



#### DISEÑO

Peso de fibra	580 grs / m <sup>2</sup>
Tipo de producto construcción	Alfombra en rollo Tejido
Pedido mínimo	No aplica mínimos
Tipo de tejido	Argollado
Galga	1/10 (39.37 hilos por cada 10 cm)
Densidad	4348
Densidad de peso	104400
Puntadas por centímetro	39,4 por cada 10 cm
Altura final del tejido:	6 mm
Método de teñido	Teñido en seco previo
Base de material	Algodón con polipropileno
Tipo de fibra	Olefin - Permastrand
Repetición de patrón	No aplicable
Dimensiones	32,74 x 3,66 Mts
Método de instalación	No aplica
Tecnología contra decoloración:	Sentry Soil Protection
Recomendación de tráfico:	Tráfico comercial alto

#### SOSTENIBILIDAD


IAQ Green Label Plus:	CRI Green Label Plus GLP1098
Contenido reciclado:	50%
NSF 140:	EcoFlex ICT - NSF 140 Gold
Marca Registrada:	Declarado

#### DESARROLLO

Estática	AATCC-134 Under 3.5 KV
Flamabilidad	16CFR-1630.4 (FF-1-70)
Densidad de Humo	ASTM E 662 Less than 450
Calidad de aire interno	GLP 7678

#### SERVICIO

Garantías:	Lifetime Limited Carpet Tile Warranty, Lifetime Limited Colorfastness to Light, 10 Year Limited Colorfastness to Atmospheric Contaminants, 10 Year Limited Stain Warranty, 10 Year Static
------------	---




Wired Out  
989



Zoom In  
968



Energizer Ready  
846



Recharge Often  
858



Buzz Worthy  
862



Power Surge  
579